INCISE SUPER MATTE SEALANT

MATERIAL SAFETY DATA SHEET



Incise Uganda Ltd Luzira Industrial Park, Kampala, Uganda 256-76622579 info@incise.ug www.incise.ug

1. IDENTIFICATION

Product name: INCISE Super Matte Sealant

Use: Decorative concrete and microcement sealant

Manufacturer: Incise Uganda Ltd

2. HAZARD IDENTIFICATION

- GHS Classification:

Flammable Liquid

Skin Irrit. 2, Eye Irrit. 2

STOT SE 3

- Signal Word: Danger

- Hazard Statements:

Highly flammable.

Causes skin and eye irritation.

May cause dizziness or drowsiness.

3. COMPOSITION / INFORMATION ON INGREDIENTS

- Xylene
- MEK (Methyl Ethyl Ketone)
- Ethyl Acetate
- Acrylic Polymer

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. Get medical advice.

Skin Contact: Wash with soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Seek medical help.

Ingestion: Do NOT induce vomiting. Rinse mouth and contact a doctor.

5. FIRE-FIGHTING MEASURES

Use dry chemical or CO2. Cool containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Eliminate ignition sources. Absorb with inert material.

7. HANDLING AND STORAGE

Store in flammable-safe area. Ground containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilate. Use gloves, goggles, and organic vapor respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Low viscosity. Flash point ~13°C. Solvent odor.

10. STABILITY AND REACTIVITY

Avoid oxidizers, heat, and open flame.

11. TOXICOLOGICAL INFORMATION

May cause CNS depression. Can irritate eyes and skin.

12. ECOLOGICAL INFORMATION

Harmful to aquatic life. Use caution.

13. DISPOSAL CONSIDERATIONS

Handle as hazardous waste. Follow regulations.

14. TRANSPORT INFORMATION

UN1263, Paint-related material, Flammable liquid.

15. REGULATORY INFORMATION

Contains SARA 313 reportable components.

16. OTHER INFORMATION

Prepared by: Incise Uganda Ltd. Rev. May 2025.

