

INCISE CEMWASH

PRODUCT DATA SHEET

APPLICATION PROCESS

Product Type: Decorative, pigmented, weatherproof cement-based wall finish

Use: Exterior and interior walls, brickwork, plaster, concrete, and architectural surfaces

1. SURFACE PREPARATION

Objective: Ensure proper adhesion and uniform finish

Steps:

- Cure plastered surfaces for at least 28 days before application
- Clean substrate to remove dust, oil, loose particles, or paint
- For brick or blockwork, rub high spots with a brick to smooth surface
- Prime surface
- Allow primer to dry thoroughly before proceeding

2. MIXING CEMWASH

Objective: Create a consistent slurry for application

Materials:

CemWash First Coat

Clean water

Steps:

- Mix CemWash powder with water in a ratio of 1 part CemWash to 1.5 parts water
- Stir continuously to form a creamy slurry
- Use a mechanical mixer for uniform consistency
- Apply all mixed material within 30 minutes; keep stirred during use

3. APPLICATION – FIRST COAT

Objective: Establish base adhesion and texture

Tools:

Block brush, broom, or hopper spray gun

Steps:

- Apply CemWash First Coat evenly using block brush
- Work from top to bottom to avoid streaks
- Clean splashes and over-coating at the end of each day
- Allow to dry for 24 hours

4. APPLICATION – TOP COAT

Objective: Achieve final color and finish

Steps:

- Mix CemWash Top Coat as per previous ratio
- Apply using block brush or sponge roller
- Maintain consistent pressure and direction for uniform texture
- Optional: Use a damp sponge to create desired mottled or textured effect
- Avoid patching once dry—use two applicators per wall (top and bottom) for seamless finish

5. CURING

Objective: Prevent cracking and ensure durability

Steps:

- Mist spray the wall with clean water 3 times the day after final coat
- Cure from bottom to top to avoid water run marks
- Protect from direct rain or harsh sun during curing

6. SEALING (OPTIONAL)

Objective: Enhance stain resistance and longevity

Steps:

- Apply water-based sealer if wall is exposed to heavy dirt or moisture
- Use roller or brush for uniform coverage
- Allow full curing between coats

POINTS TO NOTE:

- **Finish:** Natural mottled texture with subtle color movement
- **Durability:** UV-resistant, weatherproof, and low-maintenance
- **Application Method:** Brush or spray (hopper gun with 3 mm nozzle)
- **Substrate Compatibility:** Brick, block, plaster, concrete, previously painted surfaces